



Packing


Imballo

Weight with box (EXTREME 2D 1,5HP) :

51 Kg - 112,4 Lbs

Box dimensions cm : 60 x 45 x 86 (0,23 m³)

Quantity per (110x110) PALLET : 8 pc.

| Dental unit  | Pneumatic | | |
|--|--------------------|---|---|
| | Electric-Pneumatic | | |
| | Electric | | |
| EXTREME 0,75 CV | 1 | X | X |
| EXTREME 1,50 CV | 2 | 1 | 1 |
| EXTREME 2,00 CV | 2 | 2 | 1 |
| EXTREME 2,50 CV | 4 | 3 | 2 |
| EXTREME 3,00 CV | 6 | 4 | 3 |

| Compressor Model | Tank | Dryer | Cylinders | Air Intake | Air delivery | Pressure | Power | Phase | Noise | Weight | Dimensions |
|---------------------|--------|----------|-----------|-----------------|--|-----------|-------------|-----------|--------|-----------|----------------|
| Modello Compressore | Serb. | Essicat. | Cilindri | Aria Aspirata | Aria resa | Pressione | Motore | Fase | Rumore | Peso | Dimensioni |
| Type | Liters | Complete | N° | l/min. - C.F.M. | l/min. - C.F.M. | Bar - Psi | HP - kW | Tippe | dB | Kg - Lbs | cm (LxWxH) |
| EXTREME 2V 50L 0,75 | 50 | X | 2 | 200 - 7,0 | 60 - 2,1 (5 BAR) 42 - 1,5 (8 BAR) | 8 - 114 | 0,75 - 0,5 | Single | 72 | 36,5 - 81 | 46 x 43 x 83 |
| EXTREME 2D 50L 0,75 | 50 | ✓ | 2 | 200 - 7,0 | 60 - 2,1 (5 BAR) 42 - 1,5 (8 BAR) | 8 - 114 | 0,75 - 0,5 | Single | 72 | 45 - 99 | 58,5 x 43 x 83 |
| EXTREME 2V 50L 1,50 | 50 | X | 2 | 240 - 8,5 | 125 - 4,4 (5 BAR) 100 - 3,5 (8 BAR) | 8 - 114 | 1,50 - 1,1 | Single | 72 | 39,5 - 87 | 46 x 43 x 83 |
| EXTREME 2D 50L 1,50 | 50 | ✓ | 2 | 240 - 8,5 | 125 - 4,4 (5 BAR) 100 - 3,5 (8 BAR) | 8 - 114 | 1,50 - 1,1 | Single | 72 | 48 - 106 | 58,5 x 43 x 83 |
| EXTREME 2V 50L 2,00 | 50 | X | 2 | 350 - 12,4 | 156 - 5,5 (5 BAR) 127 - 4,5 (8 BAR) | 8 - 114 | 2,00 - 1,5 | Single | 73 | 42,5 - 94 | 46 x 43 x 83 |
| EXTREME 2D 50L 2,00 | 50 | ✓ | 2 | 350 - 12,4 | 156 - 5,5 (5 BAR) 127 - 4,5 (8 BAR) | 8 - 114 | 2,00 - 1,5 | Single | 73 | 51 - 112 | 58,5 x 43 x 83 |
| EXTREME 2V 50L 2,50 | 50 | X | 4 | 480 - 17,0 | 240 - 8,5 (5 BAR) 190 - 6,7 (8 BAR) | 8 - 114 | 2,50 - 1,84 | Single | 73 | 52 - 115 | 64 x 45 x 89 |
| EXTREME 2D 50L 2,50 | 50 | ✓ | 4 | 480 - 17,0 | 240 - 8,5 (5 BAR) 190 - 6,7 (8 BAR) | 8 - 114 | 2,50 - 1,84 | Single | 73 | 60 - 132 | 64 x 45 x 89 |
| EXTREME 2V 50L 3,00 | 50 | X | 4 | 600 - 21,2 | 373 - 13 (5 BAR) 330 - 12 (8 BAR) | 10 - 145 | 3,00 - 2,2 | Three | 73 | 54 - 119 | 64 x 45 x 89 |
| EXTREME 2D 50L 3,00 | 50 | ✓ | 4 | 600 - 21,2 | 373 - 13 (5 BAR) 330 - 12 (8 BAR) | 10 - 145 | 3,00 - 2,2 | Three + N | 73 | 62 - 136 | 64 x 45 x 89 |

With automatic thermal protection

Con protezione termica automatica